

# Technical Specifications

|                        |   |
|------------------------|---|
| Adapters included      | See Dropdown Options for USB-C and Lightning Cable Options  |
| Cable connector length | Various   |
| Cable connectors       | USBC-USBC Right Angle Cable   |
| Connector Types        | USB-C Power + Data (Power Delivery) / USB-C Fast Charging Only  |
| Data + PoE Ports       | 1 (Input) / 1 (Output)  |
| Data Rate              | 10/100 Mbps   |
| Data Standard          | USB 2.0 (Output)  |
| Dimensions             | 2.25×1.75×1.25 in   |
| Input Voltage Range    | 44-57v PoE  |
| Max Power for Kit      | 25 Watts / USBC negotiations (5V2.6A, 9V1.78A, 12V1.34A,15V1.37A, 20V1.15A)                           |
| Mount Type             | Junction Box Receptacle   |
| Operating Humidity     | 10 – 90%  |
| Operating Temperature  | -10 to 40°C   |
| Output Voltage         | USB-C (5V2.6A, 9V1.78A, 12V1.34A,15V1.37A, 20V1.15A)  |
| PoE Method             | IEEE 802.3at; PoE+  |
| PoE Mode/Pinout        | Mode A/B  |
| PoE Standard           | IEEE 802.3at  |
| Power Input            | On Power Only Port – For devices drawing < 15 watts – Lenovo M10, MicroUSB devices, iPad 10.2 or Mini |
| Storage Temperature    | -30 to 70°C   |
| Weight                 | 1.75 oz.  |